

# 2019 Annual Groundwater Monitoring and Corrective Action Report Addendum No. 1

Ottumwa Generating Station – Zero Liquid Discharge Pond  
Ottumwa, Iowa

Prepared for:

Alliant Energy



**SCS ENGINEERS**

25222072.00 | May 4, 2022

2830 Dairy Drive  
Madison, WI 53718-6751  
608-224-2830

## Table of Contents

Section	Page
<b>1.0 Introduction.....</b>	<b>1</b>

### Tables

Table 1	Groundwater Monitoring Well Network
Table 2	Groundwater Elevation Summary
Table 3	Horizontal Gradients and Flow Velocities
Table 4	Groundwater Analytical Results Summary - 2019
Table 5	2019 Groundwater Field Data Summary

### Figures

Figure 1	Site Location Map
Figure 2	Site Plan and Monitoring Well Location
Figure 3	Shallow Potentiometric Surface, April 8, 2019
Figure 4	Shallow Potentiometric Surface, October 23-24, 2019

### Appendices

Appendix A	Regional Hydrogeologic Information
Appendix B	Boring Logs and Well Construction Documentation
Appendix C	Historical Monitoring Results
Appendix D	Statistical Evaluation

I:\25222072.00\Deliverables\2019 Fed Annual Report Addendum - OGS ZLDP\220504\_Annual CCR GW Report OGS ZLDP\_2019 Add 1.docx

## 1.0 INTRODUCTION

This 2019 Annual Groundwater Monitoring and Corrective Action Report Addendum (Addendum) was prepared to support compliance with the groundwater monitoring requirements of the Coal Combustion Residuals (CCR) Rule [40 CFR 257.50-107]. The original 2019 Annual Groundwater Monitoring and Corrective Report (Annual Report) was completed on January 31, 2020, to fulfill the requirements of 40 CFR 257.90(e).

The 2019 Annual Report and this Addendum cover the period of groundwater monitoring from January 1, 2019, through December 31, 2019.

This Addendum includes the following tables, figures, and appendix materials to support the information in the original 2019 Annual Report:

- Table 1 – Groundwater Monitoring Well Network
- Table 2 – Groundwater Elevation Summary
- Table 3 – Horizontal Gradients and Flow Velocities
- Table 4 – Groundwater Analytical Results Summary - 2019
- Table 5 – 2019 Groundwater Field Data Summary
- Figure 1 – Site Location Map
- Figure 2 – Site Plan and Monitoring Well Location
- Figure 3 – Shallow Potentiometric Surface, April 8, 2019
- Figure 4 – Shallow Potentiometric Surface, October 23-24, 2019
- Appendix A – Regional Hydrogeologic Information
- Appendix B – Boring Logs and Well Construction Documentation
- Appendix C – Historical Monitoring Results
- Appendix D – Statistical Evaluation

## Tables

- 1 Groundwater Monitoring Well Network
- 2 Groundwater Elevation Summary
- 3 Horizontal Gradients and Flow Velocities
- 4 Groundwater Analytical Results Summary - 2019
- 5 2019 Groundwater Field Data Summary

**Table 1. Groundwater Monitoring Well Network  
Ottumwa Generating Station - Zero Liquid Discharge Pond /  
SCS Engineers Project #25222072.00**

<b>Monitoring Well</b>	<b>Location in Monitoring Network</b>	<b>Role in Monitoring Network</b>
MW-301	Upgradient	Background
MW-307	Downgradient	Compliance
MW-308	Downgradient	Compliance
MW-309	Downgradient	Compliance

Created by: RM  
 Last revision by: JAO  
 Checked by: KLG

Date: 12/14/2020  
 Date: 3/22/2022  
 Date: 3/28/2022

\\Mad-fs01\data\Projects\25222072.00\Deliverables\2019 Fed Annual Report Addendum - OGS  
 ZLDP\Tables\[Table 1\_GW Monitoring Well Network.xlsx]GW Summary

**Table 2. Groundwater Elevation Summary**  
**WPL - Ottumwa Generating Station / SCS Engineers Project #25222072.00**

Ground Water Elevation in feet above mean sea level (amsl)											
Well Number	MW-301	MW-302	MW-303	MW-304	MW-305	MW-306	MW-307	MW-308	MW-309	MW-310	MW-311
<b>Top of Casing Elevation (feet amsl)</b>	686.63	673.90	661.07	682.84	683.91	683.47	657.56	655.39	654.94	658.63	654.18
<b>Screen Length (ft)</b>	10.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00
<b>Total Depth (ft from top of casing)</b>	17.0	25.8	17.5	52.3	51.5	36.6	28.0	25.0	27.5	25.9	17.9
<b>Top of Well Screen Elevation (ft)</b>	679.63	653.10	648.57	635.54	637.41	651.87	634.56	635.39	632.44	637.76	641.24
<b>Measurement Date</b>											
April 26, 2016	682.80	655.63	652.42	655.37	661.67	670.86	NI	NI	NI	NI	NI
June 23, 2016	682.58	655.65	652.89	656.53	662.36	670.64	NI	NI	NI	NI	NI
August 9, 2016	682.27	655.52	651.76	653.79	660.78	670.35	NI	NI	NI	NI	NI
October 26-27, 2016	682.04	655.67	652.17	655.03	661.37	670.21	NI	NI	NI	NI	NI
January 18-19, 2017	681.67	655.46	651.74	654.50	660.87	669.89	648.81	647.42	646.66	NI	NI
April 19-20, 2017	682.15	656.35	654.57	657.48	663.27	670.69	653.62	651.09	650.16	NI	NI
June 20-21, 2017	681.91	655.65	652.42	654.75	661.26	669.94	649.85	648.26	647.60	NI	NI
August 21-23, 2017	681.28	655.13	650.58	652.39	659.00	668.77	645.78	643.12	641.82	NI	NI
November 8, 2017	681.54	655.40	651.34	653.03	659.76	669.04	647.37	644.99	644.20	NI	NI
April 18, 2018	681.53	655.71	652.47	655.55	660.99	668.92	649.66	647.91	647.65	NI	NI
May 30, 2018	NM	NM	NM	NM	NM	NM	652.45	651.05	650.98	NI	NI
June 28, 2018	NM	NM	NM	NM	NM	NM	652.87	651.43	651.47	NI	NI
July 18, 2018	NM	NM	NM	NM	NM	NM	652.27	650.67	650.69	NI	NI
August 14-15, 2018	680.91	656.05	652.57	656.35	661.56	668.66	NM	NM	NM	NI	NI
August 29, 2018	681.09	655.89	655.07	657.82	NM	NM	NM	NM	NM	NI	NI
October 16, 2018	682.50	656.91	656.17	658.20	663.37	670.24	654.13	NM	651.61	NI	NI
January 8, 2019	682.22	656.03	654.65	656.28	662.13	669.84	NM	NM	NM	NI	NI
April 8, 2019	682.69	657.23	655.55	659.33	664.01	670.96	654.90	653.70	653.55	NI	NI
August 28, 2019	NM	NM	NM	NM	NM	NM	NM	NM	NM	640.98	642.10
October 23-24, 2019	683.07	660.14	653.86	657.71	663.21	671.28	651.89	651.31	651.28	649.31	647.80
December 11, 2019	NM	NM	NM	NM	NM	NM	649.59	647.39	647.24	NM	NM
<b>Bottom of Well Elevation (ft)</b>	669.63	648.10	643.57	630.54	632.41	646.87	629.56	630.39	627.44	632.76	636.24

Notes:

NM = not measured

NI = not installed

Created by: MDBLast rev. by: NDKChecked by: KLG

Proj Mgr QA/QC: \_\_\_\_\_

Date: 5/1/2017Date: 3/25/2022Date: 3/28/2022

Date: \_\_\_\_\_

I:\25222072.00\Deliverables\2019 Fed Annual Report Addendum - OGS ZLDP\Tables\[Table 2\_ZLDP - GW elevation Summary.xls]levels

**Table 3. Horizontal Gradients and Flow Velocity  
Ottumwa Generating Station - Zero Liquid Discharge Pond /  
SCS Engineers Project #25222072.00  
January - December 2019**

Sampling Dates	Shallow				
	h1 (ft)	h2 (ft)	Δl (ft)	Δh/Δl (ft/ft)	V (ft/d)
April 9, 2019	670.00	654.90	455	0.03	0.23
April 9, 2019	665.00	653.70	387	0.03	0.21
October 23-24, 2019	671.28	650.00	621	0.03	0.24
October 23-24, 2019	660.00	651.28	517	0.02	0.12

	Well	K Values (cm/sec)	K Values (ft/d)	Assumed Unconsolidated Porosity, n
Upgradient Well	MW-301	4.6E-03	13	
Shallow Wells	MW-302	3.2E-03	9.1	
	MW-303	1.2E-04	0.35	
	MW-304	3.5E-04	0.98	
	MW-305	2.5E-03	7.1	
	MW-306	2.8E-03	8.1	
	Geometric Mean	1.0E-03	2.8	

Note: Geometric mean calculations do not include upgradient well MW-301

Note: Multiple gradients were measured for each date to account for variation across the site

Groundwater flow velocity equation:  $V = [K*(\Delta h/\Delta l)] / n$

ft = feet

h1, h2 = point interpreted groundwater elevation

ft/d = feet per day

K = hydraulic conductivity

Δl = distance between location 1 and 2

n = effective porosity


Δh/Δl = hydraulic gradient

V = groundwater flow velocity

Created by: <u>NDK</u>	Date: <u>3/30/2022</u>
Last revision by: <u>JAO</u>	Date: <u>4/11/2022</u>
Checked by: <u>NDK</u>	Date: <u>4/18/2022</u>

**Table 4. Groundwater Analytical Results Summary - CCR Program  
Ottumwa Generating Station - Zero Liquid Discharge Pond (ZLDP) / SCS Engineers Project #25222072.00**

Parameter Name	UPL		Background Well		Compliance Wells								
			MW-301		MW-307			MW-308			MW-309		
			4/8/2019	10/24/2019	4/8/2019	10/23/2019	12/11/2019	4/8/2019	10/23/2019	12/11/2019	4/8/2019	10/23/2019	12/11/2019
<b>Appendix III</b>													
Boron, ug/L	820	UPL only	380	680	240	200	190 J	190 J	220	160 J	1,500	1,300	1,100
Calcium, mg/L	78.7		43	78	240	230	230	240	240	220	160	150	150
Chloride, mg/L	86.8		50	110	220	220	200	160	160	150	72	74	66
Fluoride, mg/L	0.484		0.44 J	<0.23	0.28 J	<0.23	<0.23	<0.23	<0.23	<0.23	0.27 J	<0.23	<0.23
Field pH, Std. Units	6.87		6.61	6.33	6.76	6.68	6.37	6.90	6.78	6.55	7.18	6.98	6.67
Sulfate, mg/L	199		81	130	100	95	92	300	300	280	410	400	370
Total Dissolved Solids, mg/L	628		340	510	1,000	1,000	1,000	1,200	1,100	1,100	1,100	1,100	980
<b>Appendix IV</b>	<b>UPL</b>	<b>GPS</b>											
Antimony, ug/L	0.22	6	<1.00	<0.53	NA	NA	<0.53	NA	NA	<0.53	NA	NA	<0.53
Arsenic, ug/L	0.53	10	<2.00	<0.75	NA	NA	<0.75	NA	NA	<0.75	NA	NA	1.1 J
Barium, ug/L	68.8	2,000	25.5	56	NA	NA	140	NA	NA	130	NA	NA	54
Beryllium, ug/L	LOQ (varies by well)	4	<1.00	<0.27	NA	NA	<0.27	NA	NA	<0.27	NA	NA	<0.27
Cadmium, ug/L	0.12	5	<0.500	0.040 J1	NA	NA	<0.039	NA	NA	<0.039	NA	NA	0.090 J
Chromium, ug/L	1.07	100	<5.00	<0.98	NA	NA	<0.98	NA	NA	5.9	NA	NA	1.7 J
Cobalt, ug/L	4.1	6	<0.500	0.60	NA	NA	11	NA	NA	0.26 J	NA	NA	3.7
Fluoride, mg/L	0.484	4	<0.500	<0.23	NA	<0.23	<0.23	NA	<0.23	<0.23	NA	<0.23	<0.23
Lead, ug/L	0.1	15	<0.500	<0.27	NA	NA	0.71	NA	NA	0.52	NA	NA	2.8
Lithium, ug/L	34.2	40	15.5	24	NA	NA	12	NA	NA	16	NA	NA	8.2 J
Mercury, ug/L	LOQ (varies by well)	2	<0.200	<0.10	NA	NA	<0.10	NA	NA	<0.10	NA	NA	<0.10
Molybdenum, ug/L	1.74	100	<2.00	1.1 J1	NA	NA	<1.1	NA	NA	<1.1	NA	NA	<1.1
Selenium, ug/L	8.55	50	<5.00	6.2	NA	NA	<1.0	NA	NA	<1.0	NA	NA	<1.0
Thallium, ug/L	0.14	2	<1.00	<0.27	NA	NA	<0.27	NA	NA	<0.27	NA	NA	<0.27
Radium 226/228 Combined, pCi/L	2.15	5	NA	0.956	NA	NA	2.46	NA	NA	2.73	NA	NA	1.77

 Blue highlighted cell indicates the compliance well result exceeds the UPL and the LOQ.

 Yellow highlighted cell indicates the compliance well result exceeds the GPS.

Abbreviations:

UPL = Upper Prediction Limit  
LOD = Limit of Detection

GPS = Groundwater Protection Standard  
LOQ = Limit of Quantitation

ug/L = micrograms per liter  
mg/L = milligrams per liter

Notes:

J = Estimated concentration at or above the LOD and below the LOQ.

J1 = Result is less than the reporting limit but greater than or equal to the method detection limit and the concentration is an approximate value.

Created by: <u>NDK</u>	Date: <u>6/12/2019</u>
Last revision by: <u>JAO</u>	Date: <u>3/30/2022</u>
Checked by: <u>MDB</u>	Date: <u>3/30/2022</u>
Proj Mgr QA/QC: _____	Date: _____

I:\25222072.00\Deliverables\2019 Fed Annual Report Addendum - OGS ZLDP\Tables\[Table 4\_GW Monitoring Summary.xlsx]Table



**Table 5. 2019 Groundwater Field Data Summary  
Ottumwa Generating Station - Zero Liquid Discharge Pond  
SCS Engineers Project #25222072.00**

Well	Sample Date	Groundwater Elevation (feet)	Field Temperature (deg C)	Field pH (Std. Units)	Oxygen, Dissolved (mg/L)	Field Specific Conductance (umhos/cm)	Field Oxidation Potential (mV)	Turbidity (NTU)
MW-301	1/8/2019	682.22	7.88	5.68	5.68	310	118.3	0.77
	4/8/2019	682.69	7.27	6.61	8.32	501	37.6	1.87
	10/24/2019	683.07	13.71	6.33	4.94	902	9.9	1.60
MW-307	4/8/2019	654.9	12.47	6.76	0.51	1599	-3.7	26
	10/23/2019	651.89	13.38	6.68	0.25	1684	-24.8	12.5
	12/11/2019	649.59	11.5	6.37	0.18	1576	-45.8	43.13
MW-308	4/8/2019	653.7	12.54	6.9	0.66	1539	-23	6.87
	10/23/2019	651.31	13.16	6.78	4.42	1637	-38.7	7.42
	12/11/2019	647.39	10.5	6.55	0.43	1532	-56.6	15.72
MW-309	4/8/2019	653.55	12.4	7.18	0.66	1396	-3.3	72.1
	10/23/2019	651.28	12.83	6.98	0.36	1461	-27.5	42.6
	12/11/2019	647.24	11.5	6.67	0.26	1350	-37.8	413.6


Created by: JAO  
 Last revision by: JAO  
 Checked by: KLG

Date: 3/23/2022  
 Date: 3/23/2022  
 Date: 3/28/2022

I:\25222072.00\Deliverables\2019 Fed Annual Report Addendum - OGS ZLDP\Tables\[Table 5\_Field\_Parameters.xlsx]Sheet1

## Figures


- 1 Site Location Map
- 2 Site Plan and Monitoring Well Location
- 3 Shallow Potentiometric Surface, April 8, 2019
- 4 Shallow Potentiometric Surface, October 23-24, 2019



**SITE LOCATION**




CHILLICOTHE QUADRANGLE  
 IOWA—WAPELLO CO.  
 7.5 MINUTE SERIES (TOPOGRAPHIC)  
 2018  
 SCALE: 1" = 2,000'




CLIENT	INTERSTATE POWER AND LIGHT CO. 20775 POWER PLANT ROAD OTTUMWA, IA 52501		SITE	ALLIANT ENERGY OTTUMWA GENERATING STATION OTTUMWA, IOWA		ENGINEER	SITE LOCATION MAP	
	PROJECT NO.	25219072.00		DRAWN BY:	BSS		SCS ENGINEERS 2830 DAIRY DRIVE MADISON, WI 53718-6751 PHONE: (608) 224-2830	FIGURE
DRAWN:	11/15/2019	CHECKED BY:	MDB	APPROVED BY:	TK 01/30/2020			
REVISED:	01/10/2020							

I:\25219072.00\Drawings\CCR 2019 Annual Report\Site Location Map.dwg, 1/30/2020 3:51:43 PM




LEGEND	
	CCR UNIT
	CCR ZLDP MONITORING WELL
	CCR ASH POND MONITORING WELL
	CCR BACKGROUND MONITORING WELL

- NOTES:
- 2014 AERIAL PHOTOGRAPH SOURCES: ESRI, DIGITALGLOBE, GEOEYE, I-CUBED, USDA FSA, USGS, AEX, GETMAPPING, AERGRID, IGN, IGP, SWSSTOPO, AND THE GIS USER COMMUNITY.
  - CCR UNIT LIMITS ARE APPROXIMATE.
  - MONITORING WELLS MW-301, MW-302, AND MW-304, WERE INSTALLED BY CASCADE DRILLING, LLP. UNDER THE SUPERVISION OF SCS ENGINEERS FROM NOVEMBER 11-12, 2015.
  - MONITORING WELLS MW-303 AND MW-305 WERE INSTALLED BY CASCADE DRILLING LLP. UNDER THE SUPERVISION OF SCS ENGINEERS FROM DECEMBER 7-8, 2015.
  - MONITORING WELLS MW-307, MW-308, AND MW-309 WERE INSTALLED BY CASCADE DRILLING, LLP. UNDER THE SUPERVISION OF SCS ENGINEERS FROM OCTOBER 25-27, 2016.
  - THE BACKGROUND MONITORING WELL FOR THE OGS ZLDP IS MW-301.




PROJECT NO. 25222072.00	DRAWN BY: KP	<b>SCS ENGINEERS</b> 2830 DAIRY DRIVE MADISON, WI 53718-6751 PHONE: (608) 224-2830	CLIENT: INTERSTATE POWER AND LIGHT CO. 20775 POWER PLANT ROAD OTTUMWA, IA 52501	SITE: ALLIANT ENERGY OTTUMWA GENERATING STATION OTTUMWA, IOWA	SITE PLAN AND MONITORING WELL LOCATIONS-ZERO LIQUID DISCHARGE POND	FIGURE 2
DRAWN: 04/06/2022	CHECKED BY: NDK					
REVISED: 04/06/2022	APPROVED BY: TK 5/3/2022					



- LEGEND**
- CCR UNIT
  - + CCR ZLDP MONITORING WELL
  - + CCR ASH POND MONITORING WELL
  - + CCR BACKGROUND MONITORING WELL
  - 682.15** POTENTIOMETRIC ELEVATION AT WELL (APRIL 8, 2019)
  - POTENTIOMETRIC SURFACE CONTOUR
  - APPROXIMATE GROUNDWATER FLOW DIRECTION


**NOTE:**

- THE BACKGROUND MONITORING WELL FOR THE OGS ZLDP IS MW-301.



PROJECT NO.	25222072.00	DRAWN BY:	KP	<b>SCS ENGINEERS</b> 2830 DAIRY DRIVE MADISON, WI 53718-6751 PHONE: (608) 224-2830	CLIENT INTERSTATE POWER AND LIGHT CO. 20775 POWER PLANT ROAD OTTUMWA, IA 52501	SITE ALLIANT ENERGY OTTUMWA GENERATING STATION OTTUMWA, IOWA	SHALLOW POTENTIOMETRIC SURFACE APRIL 8, 2019	FIGURE
DRAWN:	04/06/2022	CHECKED BY:	NDK					3
REVISED:	04/06/2022	APPROVED BY:	TK 5/3/2022					


I:\25222072.00\Drawings\Potentiometric Surface ZLDP.dwg, 4/8/2022 8:20:00 AM



- LEGEND**
- CCR UNIT
  - + CCR ZLDP MONITORING WELL
  - + CCR ASH POND MONITORING WELL
  - + CCR BACKGROUND MONITORING WELL
  - ⊕ RIVER ELEVATION MEASUREMENT LOCATION
  - 683.07** POTENTIOMETRIC ELEVATION AT WELL (OCTOBER 23-24, 2019)
  - POTENTIOMETRIC SURFACE CONTOUR
  - APPROXIMATE GROUNDWATER FLOW DIRECTION


**NOTE:**

1. THE BACKGROUND MONITORING WELL FOR THE OGS ZLDP IS MW-301.



PROJECT NO.	25222072.00	DRAWN BY:	KP	<b>SCS ENGINEERS</b>	CLIENT:	INTERSTATE POWER AND LIGHT CO. 20775 POWER PLANT ROAD OTTUMWA, IA 52501	SITE:	ALLIANT ENERGY OTTUMWA GENERATING STATION OTTUMWA, IOWA	SHALLOW POTENTIOMETRIC SURFACE OCTOBER 23-24, 2019	FIGURE 4
DRAWN:	03/26/2022	CHECKED BY:	NDK	2830 DAIRY DRIVE MADISON, WI 53718-6751 PHONE: (608) 224-2830						
REVISED:	03/26/2022	APPROVED BY:	TK 5/3/2022							

I:\25222072.00\Drawings\Potentiometric Surface ZLDP.dwg, 4/8/2022 8:20:05 AM



Appendix A  
Regional Hydrogeologic Information


**Table OGS-2. Regional Hydrogeologic Stratigraphy  
Ottumwa Midland Landfill / SCS Engineers Project #25215053.01**

Age of Rocks	Hydrogeologic Unit	General Thickness (feet)	Name of Rock Unit*	Type of Rock
Quaternary (0-1 million years old)	Surficial Aquifers • Alluvial • Buried-Channel • Drift	0 to 320	Undifferentiated	<ul style="list-style-type: none"> <li>• Sand, gravel, silt, and clay</li> <li>• Sand, gravel, silt, and clay</li> <li>• Till (sandy, pebbly clay), sand, and silt</li> </ul>
Pennsylvanian (180 to 310 million years old)	Aquiclude	0 to 370	Undifferentiated	<ul style="list-style-type: none"> <li>• Shale, sandstone, limestone, and coal</li> </ul>
Mississippian (310 to 345 million years old)	Mississippian Aquifer • Upper	0 to 600	St. Louis Spergen	<ul style="list-style-type: none"> <li>• Limestone and sandstone</li> <li>• Limestone</li> </ul>
	• Lower		Warsaw Keokuk Burlington Hampton Starrs Cave	<ul style="list-style-type: none"> <li>• Shale and dolomite</li> <li>• Dolomite, limestone, and shale</li> <li>• Dolomite and limestone</li> <li>• Limestone and dolomite</li> <li>• Limestone</li> </ul>
	Aquiclude	0 to 425	Prospect Hill McCraney	<ul style="list-style-type: none"> <li>• Siltstone</li> <li>• Limestone</li> </ul>
Devonian (345 to 400 million years old)	Aquiclude	110 to 420	Yellow Spring Lime Creek	<ul style="list-style-type: none"> <li>• Shale, dolomite, and siltstone</li> <li>• Dolomite and shale</li> </ul>
	Devonian Aquifer		Cedar Valley Wapsipinicon	<ul style="list-style-type: none"> <li>• Limestone and dolomite</li> <li>• Dolomite, limestone, shale, and gypsum</li> </ul>
Silurian (400 to 425 million years old)		0 to 105	Undifferentiated	<ul style="list-style-type: none"> <li>• Dolomite</li> </ul>
Ordovician (425 to 500 million years old)	Aquiclude	150 to 600	Maquoketa Galena Decorah Platteville	<ul style="list-style-type: none"> <li>• Dolomite and shale</li> <li>• Dolomite and chert</li> <li>• Limestone and shale</li> <li>• Limestone, shale, and sandstone</li> </ul>
	Cambrian-Ordovician aquifer	750 to 1,110	St. Peter Prairie du Chien	<ul style="list-style-type: none"> <li>• Sandstone</li> <li>• Dolomite and sandstone</li> </ul>
Cambrian (500 to 600 million years old)		450 to 750+	Jordan St. Lawrence	<ul style="list-style-type: none"> <li>• Sandstone</li> <li>• Dolomite</li> </ul>
	Not considered an aquifer in southeast Iowa		Franconia Galesville Eau Claire Mt. Simon	<ul style="list-style-type: none"> <li>• Shale, siltstone, and sandstone</li> <li>• Sandstone</li> <li>• Sandstone, shale, and dolomite</li> <li>• Sandstone</li> </ul>
Precambrian (600 million to 2 billion + years old)				<ul style="list-style-type: none"> <li>• Sandstone, igneous rocks, and metamorphic rocks</li> </ul>

\*This nomenclature and classification of rock units in this report are those of the Iowa Geological Survey and do not necessarily coincide with those accepted by the U.S. Geological Survey.

Source: "Water Resources of Southeast Iowa," Iowa Geologic Survey Water Atlas No. 4.






**Legend**

**BEDROCK SURFACE ELEVATION**

ELEVATION ABOVE MEAN SEA LEVEL IN FEET


- BELOW 300
- 300 TO 400
- 400 TO 500
- 500 TO 600
- 600 TO 700
- 700 TO 800
- 800 TO 900



MAP DATA DERIVED FROM IOWA GEOLOGICAL AND WATER SURVEY  
 IOWA BEDROCK SURFACE ELEVATION AS OBTAINED  
 FROM IOWA NATURAL RESOURCES  
 GEOGRAPHIC INFORMATION SYSTEMS LIBRARY

<b>CLIENT</b>	INTERSTATE POWER AND LIGHT CO. 20775 POWER PLANT ROAD OTTUMWA, IA 52501	<b>SITE</b>	OTTUMWA GENERATING STATION OTTUMWA, IOWA	<b>SE IOWA REGIONAL BEDROCK SURFACE ELEVATION</b>
PROJECT NO.	25215053.03	DRAWN BY:	JB	<b>SCS ENGINEERS</b> <small>2830 DAIRY DRIVE MADISON, WI 53718-6751 PHONE: (608) 224-2830 FAX: (608) 224-2839</small>
DRAWN:	07/29/13	CHECKED BY:	MDB	
REVISED:	05/29/15	APPROVED BY:		
<b>ENGINEER</b>				<b>FIGURE</b>



I:\25215053\Drawings\OGS\ArcMAP\IOML-BEDROCK TOPO 8.5X11 portrait.mxd



## Legend


### MISSISSIPPIAN AQUIFER POTENTIOMETRIC SURFACE

ELEVATION ABOVE MEAN SEA LEVEL IN FEET



MAP DATA DERIVED FROM IOWA GEOLOGICAL AND WATER SURVEY  
 MISSISSIPPIAN AQUIFER POTENTIOMETRIC SURFACE ELEVATION AS OBTAINED  
 FROM IOWA NATURAL RESOURCES  
 GEOGRAPHIC INFORMATION SYSTEMS LIBRARY



CLIENT	INTERSTATE POWER AND LIGHT CO. 20775 POWER PLANT ROAD OTTUMWA, IA 52501	SITE	OTTUMWA GENERATING STATION OTTUMWA, IOWA	SE IOWA REGIONAL MISSISSIPPIAN AQUIFER POTENTIOMETRIC SURFACE ELEVATION	
	PROJECT NO. 25215053.03		DRAWN BY: JB	<b>SCS ENGINEERS</b>	FIGURE
DRAWN: 07/29/13	CHECKED BY: MDB				
REVISED: 05/29/15	APPROVED BY:	2830 DAIRY DRIVE MADISON, WI 53718-6751 PHONE: (608) 224-2830 FAX: (608) 224-2839			



### Legend

### MISSISSIPPIAN AQUIFER ELEVATION


ELEVATION ABOVE MEAN SEA LEVEL IN FEET



MAP DATA DERIVED FROM IOWA GEOLOGICAL AND WATER SURVEY  
 MISSISSIPPIAN AQUIFER SURFACE ELEVATION AS OBTAINED  
 FROM IOWA NATURAL RESOURCES  
 GEOGRAPHIC INFORMATION SYSTEMS LIBRARY

CLIENT	INTERSTATE POWER AND LIGHT CO. 20775 POWER PLANT ROAD OTTUMWA, IA 52501		SITE	OTTUMWA GENERATING STATION OTTUMWA, IOWA		ENGINEER	SE IOWA REGIONAL MISSISSIPPIAN AQUIFER SURFACE ELEVATION	
	PROJECT NO.	25215053.03		DRAWN BY:	JB		SCS ENGINEERS	FIGURE
	DRAWN:	07/29/13		CHECKED BY:	MDB			
REVISD:	05/29/15	APPROVED BY:						

I:\25215053\Drawings\OGS\ArcMAP\OML-MISSISS TOPO 8.5X11 portrait.mxd



Appendix B  
Boring Logs and Well Construction Documentation

Route To: Watershed/Wastewater  Waste Management   
Remediation/Redevelopment  Other

Facility/Project Name <b>IPL- Ottumwa Generating Station</b> SCS#: 25215135.40		License/Permit/Monitoring Number		Boring Number <b>MW-301</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Todd Schmalfeld Cascade Drilling</b>		Date Drilling Started <b>11/10/2015</b>		Date Drilling Completed <b>11/10/2015</b>	
Unique Well No.		DNR Well ID No.		Common Well Name <b>MW-301</b>	
Final Static Water Level <b>Feet</b>		Surface Elevation <b>684.3 Feet</b>		Borehole Diameter <b>8.5 in</b>	
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane <b>400,077 N, 1,899,709 E S/C/N</b>		Lat _____ ° _____ ' _____ "		Local Grid Location <input type="checkbox"/> N <input type="checkbox"/> E <input type="checkbox"/> S <input type="checkbox"/> W	
NW 1/4 of SW 1/4 of Section <b>26, T 73 N, R 15 W</b>		Long _____ ° _____ ' _____ "		Feet _____ Feet _____	
Facility ID		County <b>Wapello</b>		Civil Town/City/ or Village <b>Ottumwa</b>	

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
			1	TOPSOIL.	TOPSOIL									
S1	10	woh 1 39	1-6	SANDY SILT WITH GRAVEL, gray (7.5YR 6/1), gravel is fine.	ML							W		
S2	13	24 50	7-8	WEATHERED SANDSTONE, very weak, light gray matrix (10YR 7/1), secondary color very dark gray 910YR 3/1), massive.								W		
S3	5	50	10-11		SANDSTONE							W		
S4	6	50	13-14									W		
S5	4	50	15	Endo of Boring at 15 feet bgs.								W		

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53718	Tel: (608) 224-2830 Fax:
---------------	--	-----------------------------

Route To:  Watershed/Wastewater  Waste Management   
 Remediation/Redevelopment  Other

Facility/Project Name <b>IPL- Ottumwa Generating Station</b> SCS#: 25215135.40		License/Permit/Monitoring Number		Boring Number <b>MW-302</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Todd Schmalfeld Cascade Drilling</b>		Date Drilling Started <b>11/10/2015</b>		Date Drilling Completed <b>11/10/2015</b>	
Unique Well No.		DNR Well ID No.		Common Well Name <b>MW-302</b>	
Final Static Water Level <b>Feet</b>		Surface Elevation <b>671.6 Feet</b>		Borehole Diameter <b>8.5 in</b>	
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane <b>400,267 N, 1,902,625 E S/C/N</b>		Lat <b>° ' "</b>		Local Grid Location <input type="checkbox"/> N <input type="checkbox"/> E <input type="checkbox"/> S <input type="checkbox"/> W	
NE 1/4 of SE 1/4 of Section 26, T 73 N, R 15 W		Long <b>° ' "</b>		Feet <input type="checkbox"/> Feet <input type="checkbox"/> Feet <input type="checkbox"/> Feet <input type="checkbox"/> W	
Facility ID		County <b>Wapello</b>		Civil Town/City/ or Village <b>Ottumwa</b>	

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments	
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200		
			1	TOPSOIL.	TOPSOIL										
			2	LEAN CLAY WITH SAND, dark gray (10YR 4/1).											
			3												
			4												
			5												
			6												
			7												
			8		CL										
			9												
			10												
S1	19	14 57	11									M			
			12												
S2	19	24 711	13									M			
			14	LEAN CLAY WITH SAND, very dark gray (5Y 3/1).											
			15		CL										
			16												

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53718	Tel: (608) 224-2830 Fax:
---------------	---	-----------------------------

Boring Number MW-302

Page 2 of 2

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S3	24	23 99	17	POORLY GRADED SAND, olive yellow (2.5Y 6/6).	SP				M					
			18	LEAN CLAY, dark grayish brown (10YR 4/2).	CL									
S4	24	44 44	19	POORLY GRADED GRAVEL, fine.	GP				W				saturation @ 18 ft bgs.	
			20	LEAN CLAY, brownish yellow (10YR 6/8).	CL									
S5	15	23 36	21	POORLY GRADED GRAVEL WITH CLAY, gray (10YR 5/1), fine.					W					
			22		GP-GC									
S6	24	34 89	23						W					
			24	POORLY GRADED SAND, gray (10YR 5/1), medium grained.										
S7	24	43 68	25		SP				W					
			26											
			27											
S8	24	78 119	28	Same as above, but brown (10YR 5/3).					W					
			29	POORLY GRADED SAND, gray (10YR 5/1), fine grained, (weathered bedrock?).										
			30	Medium grained.										
S9	23	514 3350/4	31		SP				W					
			32											
S10	12	1250/3	33						W					
			34	POORLY GRADED SAND, olive yellow (2.5Y 7/1), fine grained, (weathered bedrock?).										
			35		SP									
S11	3	50/3	36						W					
			37	End of Boring at 37 feet bgs.										

Route To: Watershed/Wastewater  Waste Management   
 Remediation/Redevelopment  Other

Facility/Project Name <b>IPL- Ottumwa Generating Station</b> SCS#: 25215135.40		License/Permit/Monitoring Number		Boring Number <b>MW-303</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Todd Schmalfeld Cascade Drilling</b>		Date Drilling Started <b>12/8/2015</b>		Date Drilling Completed <b>12/8/2015</b>	
Unique Well No.		DNR Well ID No.		Common Well Name <b>MW-303</b>	
Final Static Water Level <b>Feet</b>		Surface Elevation <b>659.0 Feet</b>		Borehole Diameter <b>8.5 in</b>	
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/>		State Plane <b>400,583 N, 1,903,215 E S/C/N</b>		Local Grid Location <input type="checkbox"/> N <input type="checkbox"/> E <input type="checkbox"/> S <input type="checkbox"/> W	
NE 1/4 of SE 1/4 of Section 26, T 73 N, R 15 W		Lat _____ ' _____ "		Long _____ ' _____ "	
Facility ID		County <b>Wapello</b>		Civil Town/City/ or Village <b>Ottumwa</b>	

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments	
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200		
			1	FILL, boring location was cleared to 9' bgs by hydrovac, then back filled.	FILL										
			2												
			3												
			4												
			5												
			6												
			7												
			8												
			9												
			10	WEATHERED SANDSTONE, medium grained, brown (10YR 5/4).											
S1	1	50	11	SANDSTONE											
			12												
			13												
S2	NR		14												
				End of Boring at 14.5 ft bgs.											

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53718	Tel: (608) 224-2830 Fax:
---------------	--	-----------------------------



Route To: Watershed/Wastewater  Waste Management   
Remediation/Redevelopment  Other

Facility/Project Name <b>IPL- Ottumwa Generating Station</b> SCS#: 25215135.40		License/Permit/Monitoring Number		Boring Number <b>MW-304</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Todd Schmalfeld Cascade Drilling</b>		Date Drilling Started <b>11/11/2015</b>		Date Drilling Completed <b>11/11/2015</b>	
Unique Well No.		DNR Well ID No.		Common Well Name <b>MW-304</b>	
Final Static Water Level <b>Feet</b>		Surface Elevation <b>680.1 Feet</b>		Borehole Diameter <b>8.5 in</b>	
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane <b>401,152 N, 1,903,287 E</b> S/C/N				Local Grid Location	
SE 1/4 of NE 1/4 of Section 26, T 73 N, R 15 W				Lat _____ ' _____ " <input type="checkbox"/> N <input type="checkbox"/> E Long _____ ' _____ "      Feet <input type="checkbox"/> S      Feet <input type="checkbox"/> W	
Facility ID		County <b>Wapello</b>		Civil Town/City/ or Village <b>Ottumwa</b>	

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well	Diagram	PID/FID	Soil Properties					RQD/ Comments
										Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
			1	TOPSOIL.	TOPSOIL										
			2	FAT CLAY, black (10YR 2/1).											
			3												
			4												
			5												
			6												
			7		CH										
			8												
			9												
			10												
S1	23	4 5 4 5	11									M			
			12												
			13	FAT CLAY, yellowish brown (10YR 5/4).											
S2	19.5	4 4 5 5	14		CH							M			
			15	FAT CLAY, yellowish brown (10YR 3/4).											
			16		CH										

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53718	Tel: (608) 224-2830 Fax:
---------------	--	-----------------------------

Boring Number MW-304

Page 2 of 3

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S3	12	33 45	17	FAT CLAY, yellowish brown (10YR 3/4). (continued)										
S4	22	43 712	18											
S5	23	27 89	19											
S6	23	34 86	20											
S7	23	511 1511	21											
S8	15	44 56	22											
S9	18	46 99	23											
S10	24	46 76	24											
S11	16	22 46	25											
S12	24	43 55	26											
S13	18	23 33	27											
			28											
			29											
			30											
			31											
			32											
			33											
			34											
			35											
			36	FAT CLAY, DARK OLIVE BROWN (2.5Y 3/3).										
S11	16	22 46	37											
S12	24	43 55	38											
			39											
			40											
			41											
			42											

Boring Number MW-304

Page 3 of 3


Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S14	24	34	43	FAT CLAY, DARK OLIVE BROWN (2.5Y 3/3). <i>(continued)</i>	CH									
		914	44	SANDY SILT, very dark gray.	ML					W				
S16	15	3050.4	45	POORLY GRADED SAND, medium grained, gray (5Y 6/1), (weathered bedrock).	SP									
		50.4	46											W
S17	5	3350.2	47											
		50.2	48	W										
S18		50.4	49											
		50.4	50	W										
			51											
			52	End of Boring at 52 feet bgs.										

Route To:  Watershed/Wastewater  Waste Management   
 Remediation/Redevelopment  Other

Facility/Project Name <b>IPL- Ottumwa Generating Station</b> SCS#: 25215135.40		License/Permit/Monitoring Number		Boring Number <b>MW-305</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Todd Schmalfeld Cascade Drilling</b>		Date Drilling Started <b>12/7/2015</b>		Date Drilling Completed <b>12/8/2015</b>	
Unique Well No.		DNR Well ID No.		Common Well Name <b>MW-305</b>	
Final Static Water Level <b>Feet</b>		Surface Elevation <b>681.5 Feet</b>		Borehole Diameter <b>8.5 in</b>	
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane <b>401,473 N, 1,903,023 E S/C/N</b>		Lat <input type="checkbox"/> ° <input type="checkbox"/> ' <input type="checkbox"/> "		Local Grid Location <input type="checkbox"/> N <input type="checkbox"/> E <input type="checkbox"/> S <input type="checkbox"/> W	
SE 1/4 of NE 1/4 of Section 26, T 73 N, R 15 W		Long <input type="checkbox"/> ° <input type="checkbox"/> ' <input type="checkbox"/> "		Feet <input type="checkbox"/> S <input type="checkbox"/> W	
Facility ID		County <b>Wapello</b>		Civil Town/City/ or Village <b>Ottumwa</b>	


Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth in Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments	
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200		
			1	TOPSOIL	TOPSOIL										
			1	GRAVEL	GP										
			2	FAT CLAY											
			3												
			4												
			5												
			6												
			7												
			8												
			9		CH										
			10												
			11	FAT CLAY, very dark grayish brown (10YR 3/2).									W		
S1	18	36 9 11	11												
			12												
			13												
			14	same as above except, brown (10YR 4/3).									W		
S2	22	37 14 22	14												
			15												
			16												

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53718	Tel: (608) 224-2830 Fax:
--	---	-----------------------------


Boring Number MW-305

Page 2 of 3

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S3	22	5 15 14 15	17	FAT CLAY (continued)										
S4	20	3 5 13 15	18 19		CH									
S5	24	4 5 7 11	20 21 22	FAT CLAY WITH SILT, dark gray (10YR 4/1).					M					
S6	20	7 11 15 20	23 24	same as above except, very dark brown (10YR 2/2).					M					
S7	24	4 8 11 12	25 26 27	same as above except, very dark gray (10YR 3/1).	CH				M					
S8	24	8 12 16 21	28 29						M					
S9	13	4 4 7 12	30 31 32						M					
S10	24	5 6 9	33 34	LEAN CLAY, very dark brown (10YR 2/2).					W					
S11	24	4 4 5 7	35 36 37		CL				W					
S12	22	2 2 3 5	38 39	same as above except, very dark grayish brown (10YR 3/2).					W					
S13	6	3 9 11	40 41 42	POORLY GRADED SANDY GRAVEL, fine, brown (10YR 4/3).	GPS				W				water @ 41.0 ft bgs.	

Boring Number MW-305

Page 3 of 3

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments			
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200				
S14	22	23 50	43	POORLY GRADED SAND, medium grained, yellowish brown (10YR 5/4), (weathered bedrock). <i>(continued)</i>	SP												
			44														
			45														
S15	6	5 10 50	46		SP												
			47														
			48														
S16	6	50	49														
			50	End of Boring at 50 ft bgs.													

**SCS ENGINEERS**

Environmental Consultants and Contractors

**SOIL BORING LOG INFORMATION**

Route To: Watershed/Wastewater  Waste Management   
 Remediation/Redevelopment  Other

Facility/Project Name <b>IPL- Ottumwa Generating Station</b> SCS#: 25215135.40		License/Permit/Monitoring Number		Boring Number <b>MW-306</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Todd Schmalfeld Cascade Drilling</b>		Date Drilling Started <b>11/12/2015</b>		Date Drilling Completed <b>11/12/2015</b>	
Unique Well No.		DNR Well ID No.		Common Well Name <b>MW-306</b>	
Final Static Water Level <b>Feet</b>		Surface Elevation <b>681.1 Feet</b>		Borehole Diameter <b>8.5 in</b>	
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane <b>401,666 N, 1,902,629 E</b> S/C/N		Lat _____ ° _____ ' _____ "		Local Grid Location <input type="checkbox"/> N <input type="checkbox"/> E <input type="checkbox"/> S <input type="checkbox"/> W	
SE    1/4 of NE    1/4 of Section    26,    T 73 N, R 15 W		Long _____ ° _____ ' _____ "		Feet    Feet    Feet	
Facility ID		County <b>Wapello</b>		Civil Town/City/ or Village <b>Ottumwa</b>	

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
			1	TOPSOIL.	TOPSOIL									
			2	FAT CLAY, dark olive brown (2.5Y 3/3).										
			3											
			4											
			5											
			6											
			7		CH									
			8											
			9											
			10											
S1	18	36 9 11	11									M		
			12											
			13	FAT CLAY, gray (10YR 5/1).								M		
S2	22	56 7 9	14		CH									
			15											
			16											

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53718	Tel: (608) 224-2830 Fax:
---------------	---	-----------------------------

Boring Number MW-306

Page 2 of 2

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S3	22	5 10 10 14	17	FAT CLAY, gray (10YR 5/1). (continued) FAT CLAY, gray (10YR 5/1).	CH				M					
S4	13	5 8 14 17	18 19	FAT CLAY, dark olive brown (2.5Y 3/3).					M					
S5	15	5 6 13 16	21 22		CH				W					
S6	15	3 5 7 9	23 24						W					
S7	22	2 5 7 11	26 27	POORLY GRADED SAND, very dark grayish brown (10YR 3/2), medium to coarse grained, (weathered bedrock?).					W					
S8	NR	7 3 4 3	28 29						W					
S9	18	1 1 2 2	31 32		SP				W					
S10	13	WOR	33 34						W					
				End of Boring at 34.5 feet bgs.										




Route To: Watershed/Wastewater  Waste Management   
Remediation/Redevelopment  Other

Facility/Project Name <b>IPL- Ottumwa Generating Station</b>		License/Permit/Monitoring Number SCS#: 25215135.40		Boring Number <b>MW-301</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Todd Schmalfeld Cascade Drilling</b>			Date Drilling Started 11/10/2015	Date Drilling Completed 11/10/2015	Drilling Method 4-1/4 hollow stem auger
Unique Well No.	DNR Well ID No.	Common Well Name <b>MW-301</b>	Final Static Water Level Feet	Surface Elevation <b>684.3 Feet</b>	Borehole Diameter <b>8.5 in</b>
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane <b>400,077 N, 1,899,709 E S/C/N</b>			Lat _____ ° _____ ' _____ "		Local Grid Location
NW 1/4 of SW 1/4 of Section 26, T 73 N, R 15 W			Long _____ ° _____ ' _____ "		Feet <input type="checkbox"/> N <input type="checkbox"/> F Feet <input type="checkbox"/> S <input type="checkbox"/> W
Facility ID		County <b>Wapello</b>	Civil Town/City/ or Village <b>Ottumwa</b>		

Sample Number and Type	Length A.t. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well	Diagram	PID/FID	Soil Properties					RQD/ Comments	
										Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200		
			1	TOPSOIL.	TOPSOIL											
S1	10	woh 1 39	2-6	SANDY SILT WITH GRAVEL, gray (7.5YR 6/1), gravel is fine.	ML						W					
S2	13	24 50	7-8	WEATHERED SANDSTONE, very weak, light gray matrix (10YR 7/1), secondary color very dark gray 910YR 3/1), massive.							W					
S3	5	50	10-11		SANDSTONE						W					
S4	6	50	13-14								W					
S5	4	50	15	Endo of Boring at 15 feet bgs.							W					

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53718	Tel: (608) 224-2830 Fax:
--	--	-----------------------------

Route To:  Watershed/Wastewater  Waste Management   
 Remediation/Redevelopment  Other

Facility/Project Name IPL-Ottumwa Generating Station SCS#: 25216148.00		License/Permit/Monitoring Number		Boring Number MW-307	
Boring Drilled By: Name of crew chief (first, last) and Firm Mike Mueller Cascade Drilling			Date Drilling Started 10/25/2016	Date Drilling Completed 10/25/2016	Drilling Method HSA
Unique Well No.	DNR Well ID No.	Common Well Name MW-307	Final Static Water Level Feet	Surface Elevation 655.1 Feet	Borehole Diameter 8.5 in
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane 401,707 N, 1,903,070 E S/C/N NE 1/4 of SE 1/4 of Section 26, T 73 N, R 15 W			Local Grid Location Lat _____ ' _____ " <input type="checkbox"/> N <input type="checkbox"/> E Long _____ ' _____ " Feet <input type="checkbox"/> S Feet <input type="checkbox"/> W		
Facility ID		County Wapello	Civil Town/City/ or Village Ottumwa		

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/Comments
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S1	24	22 32	1	POORLY GRADED SAND WITH GRAVEL, tan, fine to coarse sand and gravel, (construction fill sand to fill in hydrovac hole cleared to 8.5 ft bgs).	SP									
			2											
3														
4														
5														
6														
7														
8														
9														
10	W													
S2	14	41 44	11	LEAN CLAY, dark yellowish brown (10YR 4/4), slightly dense.	CL									
			12											
			13											
			14											
			15											

water level 6.5 ft bgs.

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature:  Firm: SCS Engineers  
 2830 Dairy Drive Madison, WI 53711 Tel: (608) 224-2830 Fax:

Boring Number MW-307

Page 2 of 2

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S3	24	1 2	16	LEAN CLAY, dark yellowish brown (10YR 4/4), slightly dense. (continued)	CL									
		2 4	17	SILT, dark yellowish brown (10YR 3/4), fine to medium sand.					W					
S4	17	3 3	18		ML									
		3	19						W			Bedrock @19.5 ft bgs.		
S5	5	50/0.5	20	SANDSTONE, dark brown (10YR 3/3),										
			21						W			More competent @20.5' -24.5' bgs.		
			22											
			23											
			24											
			25	more weathered.										
			26											
			27											
S6	1	100	28	Same as above except, gray (10YR 6/1).										
				End of boring at 28 ft bgs.										

**SCS ENGINEERS**

Environmental Consultants and Contractors

**SOIL BORING LOG INFORMATION**

Route To:  Watershed/Wastewater  Waste Management   
 Remediation/Redevelopment  Other

Facility/Project Name <b>IPL-Ottumwa Generating Station</b> SCS#: 25216148.00		License/Permit/Monitoring Number		Boring Number <b>MW-308</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Mike Mueller Cascade Drilling</b>		Date Drilling Started <b>10/25/2016</b>		Date Drilling Completed <b>10/25/2016</b>	
Unique Well No.		DNR Well ID No.		Common Well Name <b>MW-308</b>	
Final Static Water Level <b>Feet</b>		Surface Elevation <b>652.9 Feet</b>		Borehole Diameter <b>8.5 in</b>	
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane <b>402,312 N, 1,902,665 E S/C/N</b>		Lat <input type="checkbox"/> ° <input type="checkbox"/> ' <input type="checkbox"/> "		Local Grid Location <input type="checkbox"/> N <input type="checkbox"/> E <input type="checkbox"/> S <input type="checkbox"/> W	
NE 1/4 of SE 1/4 of Section 26, T 73 N, R 15 W		Long <input type="checkbox"/> ° <input type="checkbox"/> ' <input type="checkbox"/> "		Feet <input type="checkbox"/> S Feet <input type="checkbox"/> W	
Facility ID		County <b>Wapello</b>		Civil Town/City/ or Village <b>Ottumwa</b>	

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments	
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200		
			1	POORLY GRADED SAND WITH GRAVEL, tan, fine to coarse sand and gravel, (construction fill sand to fill in hydrovac hole cleared to 9.5 ft bgs).	SP										
			2												
			3												
			4												
			5												
			6												
			7												
			8												
			9												
			10	LEAN CLAY, brown (10YR 4/3), dense.	CL										
S1	24	19 4 22	11												
			12	SILT, brown (10YR 4/3), some clay.	ML										
			13												
S2	13	12 22	14												
			15												

water @ 6.5 ft bgs.

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53711	Tel: (608) 224-2830 Fax:
---------------	--	-----------------------------

Boring Number MW-308

Page 2 of 2

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S3	18	1 2	16	SILT, brown (10YR 4/3), some clay. <i>(continued)</i>	ML									
		1 3		SILTY SAND, brown (10YR 4/3).	SM					W				
			17	POORLY GRADED SAND, brown (10YR 4/3), fine grained.	SP									
S4	13	4 12	18	WELL GRADED SAND AND GRAVEL, dark grayish brown (10YR 3/2), fine to coarse grained, (weathered bedrock).	SW									
		13 3	19	SANDSTONE, dark grayish brown (10YR 4/2), weathered bedrock.						W				
S5	6	12 26	20	Same as above except, brown (10YR 4/3).										
		50/0.4	21							W				
S6	4		22											
			23											
		50/0.4	24	Same as above except, dark grayish brown (10YR 4/2).							W			
			25	End of boring at 25 ft bgs.										


Route To:  Watershed/Wastewater  Waste Management   
 Remediation/Redevelopment  Other

Facility/Project Name <b>IPL-Ottumwa Generating Station</b> SCS#: 25216148.00		License/Permit/Monitoring Number		Boring Number <b>MW-309</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Mike Mueller Cascade Drilling</b>		Date Drilling Started <b>10/27/2016</b>		Date Drilling Completed <b>10/27/2016</b>	
Unique Well No.		DNR Well ID No.		Common Well Name <b>MW-309</b>	
Final Static Water Level <b>Feet</b>		Surface Elevation <b>652.5 Feet</b>		Borehole Diameter <b>8.5 in</b>	
Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/>		State Plane <b>403,189 N, 1,902,070 E S/C/N</b>		Local Grid Location	
NE 1/4 of SE 1/4 of Section 26, T 73 N, R 15 W		Lat _____ ° _____ ' _____ "		<input type="checkbox"/> N <input type="checkbox"/> E <input type="checkbox"/> S <input type="checkbox"/> W	
Long _____ ° _____ ' _____ "		Feet		Feet	

Facility ID	County <b>Wapello</b>	Civil Town/City/ or Village <b>Ottumwa</b>
-------------	--------------------------	---

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
			1-9	Hydrovac borehole to 10 ft bgs.										
S1	3.3 6.7		10-11	LEAN CLAY, very dark grayish brown (10YR 3/2), trace sand.	CL						W			
S2	2.2 2.2		13-14								W			

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53711	Tel: (608) 224-2830 Fax:
--	--	-----------------------------

Boring Number **MW-309**

Page **2** of **2**

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S3		11 11	16	SILTY SAND, very dark grayish brown (10YR 3/2), fine to medium grained.	SM				W					
			17											
S4		35 46	18		SP				W					
			19	POORLY GRADED SAND, yellowish brown (10YR 5/4), coarse grained.										
S5		23 750	20						W					
			21											
			22	WEATHERED SANDSTONE.										
			23											
			24											
S6			25						W					
			26											
			27											
				End of boring at 27.5 ft bgs.										

**SCS ENGINEERS**

Environmental Consultants and Contractors


**SOIL BORING LOG INFORMATION**

Route To:  Watershed/Wastewater  Waste Management   
 Remediation/Redevelopment  Other

Facility/Project Name <b>IPL-Ottumwa Generating Station</b> SCS#: 25216148.00		License/Permit/Monitoring Number		Boring Number <b>B-309X</b>	
Boring Drilled By: Name of crew chief (first, last) and Firm <b>Mike Mueller Cascade Drilling</b>		Date Drilling Started <b>10/26/2016</b>		Date Drilling Completed <b>10/26/2016</b>	
Drilling Method <b>HSA</b>		Unique Well No.		DNR Well ID No.	
Common Well Name		Final Static Water Level Feet		Surface Elevation Feet	
Borehole Diameter <b>8.5 in</b>		Local Grid Origin <input type="checkbox"/> (estimated: <input type="checkbox"/> ) or Boring Location <input checked="" type="checkbox"/> State Plane		Local Grid Location	
NE 1/4 of SE 1/4 of Section 26, T 73 N, R 15 W		Lat _____ ° _____ ' _____ "		<input type="checkbox"/> N <input type="checkbox"/> E	
		Long _____ ° _____ ' _____ "		<input type="checkbox"/> S <input type="checkbox"/> W	
Facility ID		County <b>Wapello</b>		Civil Town/City/ or Village <b>Ottumwa</b>	

Sample Number and Type	Length Att. & Recovered (in)	Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
									Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S1	12	13 34	1	POORLY GRADED SAND WITH GRAVEL, tan, fine to coarse sand and gravel, (construction fill sand to fill in hydrovac hole cleared to 9 ft bgs).	SP									
			2											
			3											
S2	18	33 33	4	LEAN CLAY, dark brown (10YR 3/3), medium dense.	CL									
			5											
			6											
			7	SILT, dark brown (10YR 3/3), some clay.	ML									
			8											
			9											
			10											
			11											
			12											
			13											
			14											
			15											

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature 	Firm <b>SCS Engineers</b> 2830 Dairy Drive Madison, WI 53711	Tel: (608) 224-2830 Fax:
--	--	-----------------------------



Boring Number B-309X

Page 2 of 2

Sample		Blow Counts	Depth In Feet	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD/ Comments
Number and Type	Length Att. & Recovered (in)								Standard Penetration	Moisture Content	Liquid Limit	Plasticity Index	P 200	
S3	20	3 3	16	SILT, dark brown (10YR 3/3), some clay. <i>(continued)</i>	ML									
		3 2	17	POORLY GRADED SAND, very dark grayish brown (10YR 3/2), fine grained.	SP					W				
S4	15	1 17	18	SILT, dark brown (10YR 3/3).	ML									
		50/0.2	19	POORLY GRADED SAND, brown (10YR 4/3).	SP					W		Bedrock at 18.5 ft bgs		
S5	6	50/0.3	20	WEATHERED SANDSTONE, grayish brown (10YR 5/2).					W					
			21											
			22											
			23											
			24											
			25											
			26											
				End of boring at 26.5 ft bgs.										



IOWA DEPARTMENT OF NATURAL RESOURCES  
**MONITORING WELL/PIEZOMETER CONSTRUCTION DOCUMENTATION FORM**

Disposal Site Name: IPL - Ottumwa Generating Station Permit No.: \_\_\_\_\_

Well or Piezometer No: MW-301

Dates Started: 11/10/15 Date Completed: 11/10/15

A. SURVEYED LOCATIONS AND ELEVATIONS	B. SOIL BORING INFORMATION
Locations ( $\pm 0.5$ ft): _____ Specify corner of site: <u>SE of Parcel 003052640340000</u> Distance & direction along boundary: <u>106' W</u> Distance & direction from boundary to wall: <u>306' N</u> Elevations ( $\pm 0.01$ ft MSL): _____ Ground Surface: <u>684.28</u> Top of protective casing: <u>687.12</u> Top of well casing: _____ <u>686.63</u> Benchmark elevation: _____ Benchmark description: _____	Name & Address of Construction Company: _____ <u>Cascade Drilling, LP</u> <u>301 Alderson St</u> <u>Schofield, WI 54476</u> Name of Driller: <u>Todd Schmalfeld</u> Drilling Method: <u>HSA</u> Drilling Fluid: <u>NA</u> Bore Hole Diameter: <u>8 inch</u> Soil Sampling Method: <u>Spoon</u> Depth of Boring: <u>15 ft</u>

C. MONITORING WELL INSTALLATION	
Casing material: _____ <u>PVC sch 40</u> Length of casing: _____ <u>4 ft</u> Outside casing diameter: _____ <u>2.38"</u> Inside casing diameter: _____ <u>2"</u> Casing joint type: _____ <u>threaded</u> Casing/screen joint type: <u>threaded</u> Screen material: _____ <u>PVC</u> Screen opening size: <u>0.010"</u> Screen length: _____ <u>10 ft</u> Depth of well: _____ <u>14 ft</u> Filter Pack: _____ Material: _____ <u>Red Flint</u> Grain size: _____ <u>#40</u> Volume: _____ <u>4 cu. ft.</u> Seal (minimum 3 ft length above filter pack): _____ Material: <u>3/8 inch bentonite chips</u>	Placement method: <u>Gravity</u> Volume: <u>8 cu. ft.</u> Backfill (if different from seal): _____ Material: _____ Placement method: _____ Volume: _____ Surface seal design: _____ Material of protective casing: <u>Steel 6 inch</u> Material of grout between protective casing and well casing: <u>sand</u> Protective cap: _____ Material: <u>Steel, vented</u> Vented: <input type="checkbox"/> Yes <input type="checkbox"/> No Locking: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Well Cap: _____ Material: <u>PVC</u> Vented: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

D. GROUNDWATER MEASUREMENT ( $\pm 0.01$ ft below top of inner well casing)
Water level: <u>3.09 ft</u> Stabilization Time: <u>&lt;5 minutes</u> Well development method: <u>Surged with block and pumped to reduce turbidity. 435 gallons pumped.</u> Average depth of frostline: <u>3.5'</u>


**Attachments: Driller's log. Pipe schedules and grouting schedules. 8 1/2x11 inch map showing locations of all monitoring wells and piezometers.**

**Please mail completed for to:** Iowa Department of Natural Resources, Land Quality Bureau, 502 E 9<sup>th</sup> St, Des Moines IA 50319-0034.

**Questions? Call or Email:** Nina Koger, Environmental Engineer Sr., 515-281-8986, [Nina.Koger@dnr.iowa.gov](mailto:Nina.Koger@dnr.iowa.gov)

ELEVATIONS: ± 0.01 ft MSL  
DEPTHS: ± 0.1 ft FROM GROUND SURFACE

SPACE TO ATTACH ENTIRE SOIL BORING LOG  
(SHOW SCREENED INTERVAL AND FILTER PACK INTERVAL.)





IOWA DEPARTMENT OF NATURAL RESOURCES
MONITORING WELL/PIEZOMETER CONSTRUCTION DOCUMENTATION FORM

Disposal Site Name: IPL - Ottumwa Generating Station Permit No.:
Well or Piezometer No: MW-307
Dates Started: 10/25/16 Date Completed: 10/25/16

A. SURVEYED LOCATIONS AND ELEVATIONS B. SOIL BORING INFORMATION

Locations (± 0.5 ft):
Specify corner of site: NE of Parcel 003052620200000
Distance & direction along boundary: 683' W
Distance & direction from boundary to wall: 296' S
Elevations (± 0.01 ft MSL):
Ground Surface: 655.08
Top of protective casing: 657.58
Top of well casing: 657.56
Benchmark elevation:
Benchmark description:

Name & Address of Construction Company:
Cascade Drilling, LP
301 Alderson St
Schofield, WI 54476
Name of Driller: Mike Mueller
Drilling Method: HSA
Drilling Fluid: NA
Bore Hole Diameter: 8 inch
Soil Sampling Method: Spoon
Depth of Boring: 28 ft

C. MONITORING WELL INSTALLATION

Casing material: PVC sch 40
Length of casing: 22 ft
Outside casing diameter: 2.38"
Inside casing diameter: 2"
Casing joint type: threaded
Casing/screen joint type: threaded
Screen material: PVC
Screen opening size: 0.010"
Screen length: 5 ft
Depth of well: 27 ft
Filter Pack:
Material: Red Flint
Grain size: #40
Volume: 200 lbs
Seal (minimum 3 ft length above filter pack):
Material: 3/8 inch bentonite chips

Placement method: Gravity
Volume: 250 lbs
Backfill (if different from seal):
Material:
Placement method:
Volume:
Surface seal design:
Material of protective casing: Steel 6 inch
Material of grout between protective casing and well casing: sand
Protective cap:
Material: Steel, vented
Vented: [X] Yes [ ] No Locking: [ ] Yes [ ] No
Well Cap:
Material: PVC
Vented: [ ] Yes [X] No

D. GROUNDWATER MEASUREMENT (± 0.01 ft below top of inner well casing)

Water level: 8.12 Stabilization Time: 5 minutes
Well development method: surged with bailer and pumped
Average depth of frostline: 3.5'


Attachments: Driller's log, Pipe schedules and grouting schedules. 8 1/2x11 inch map showing locations of all monitoring wells and piezometers.

Please mail completed for to: Iowa Department of Natural Resources, Land Quality Bureau, 502 E 9th St, Des Moines IA 50319-0034.

Questions? Call or Email: Nina Koger, Environmental Engineer Sr., 515-281-8986, Nina.Koger@dnr.iowa.gov

ELEVATIONS: ± 0.01 ft MSL  
DEPTHS: ± 0.1 ft FROM GROUND SURFACE

SPACE TO ATTACH ENTIRE SOIL BORING LOG  
(SHOW SCREENED INTERVAL AND FILTER PACK INTERVAL.)





IOWA DEPARTMENT OF NATURAL RESOURCES  
**MONITORING WELL/PIEZOMETER CONSTRUCTION DOCUMENTATION FORM**

Disposal Site Name: IPL - Ottumwa Generating Station Permit No.: \_\_\_\_\_  
 Well or Piezometer No: MW-308  
 Dates Started: 10/26/16 Date Completed: 10/26/16

**A. SURVEYED LOCATIONS AND ELEVATIONS**

Locations ( $\pm 0.5$  ft): \_\_\_\_\_  
 Specify corner of site: SW of Parcel 0030502620203000  
 Distance & direction along boundary: 158' E  
 Distance & direction from boundary to wall: 417' N  
 Elevations ( $\pm 0.01$  ft MSL): \_\_\_\_\_  
 Ground Surface: 652.87  
 Top of protective casing: 655.23  
 Top of well casing: \_\_\_\_\_ 655.39  
 Benchmark elevation: \_\_\_\_\_  
 Benchmark description: \_\_\_\_\_

**B. SOIL BORING INFORMATION**

Name & Address of Construction Company: \_\_\_\_\_  
Cascade Drilling, LP  
301 Alderson St  
Schofield, WI 54476  
 Name of Driller: Mike Mueller  
 Drilling Method: HSA  
 Drilling Fluid: NA  
 Bore Hole Diameter: 8 inch  
 Soil Sampling Method: Spoon  
 Depth of Boring: 25 ft

**C. MONITORING WELL INSTALLATION**

<p>Casing material: <u>PVC sch 40</u>          Length of casing: <u>19 ft</u>          Outside casing diameter: <u>2.38"</u>          Inside casing diameter: <u>2"</u>          Casing joint type: <u>threaded</u>          Casing/screen joint type: <u>threaded</u>          Screen material: <u>PVC</u>          Screen opening size: <u>0.010"</u>          Screen length: <u>5 ft</u>          Depth of well: <u>24 ft</u>          Filter Pack: _____          Material: <u>Red Flint</u>          Grain size: <u>#40</u>          Volume: <u>200 lbs</u>          Seal (minimum 3 ft length above filter pack): _____          Material: <u>3/8 inch bentonite chips</u></p>	<p>Placement method: <u>Gravity</u>          Volume: <u>200 lbs</u>          Backfill (if different from seal): _____          Material: _____          Placement method: _____          Volume: _____          Surface seal design: _____          Material of protective casing: <u>Steel 6 inch</u>          Material of grout between protective casing and well casing: <u>sand</u>          Protective cap: _____          Material: <u>Steel, vented</u>          Vented: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No      Locking: <input type="checkbox"/> Yes <input type="checkbox"/> No          Well Cap: _____          Material: <u>PVC</u>          Vented: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No</p>
--	---

**D. GROUNDWATER MEASUREMENT ( $\pm 0.01$  ft below top of inner well casing)**

Water level: 9.85 Stabilization Time: 5 minutes  
 Well development method: surged with bailer and pumped  
 Average depth of frostline: 3.5'


**Attachments: Driller's log, Pipe schedules and grouting schedules. 8 1/2x11 inch map showing locations of all monitoring wells and piezometers.**

**Please mail completed for to:** Iowa Department of Natural Resources, Land Quality Bureau, 502 E 9<sup>th</sup> St, Des Moines IA 50319-0034.

**Questions? Call or Email:** Nina Koger, Environmental Engineer Sr., 515-281-8986, [Nina.Koger@dnr.iowa.gov](mailto:Nina.Koger@dnr.iowa.gov)

ELEVATIONS: ± 0.01 ft MSL  
DEPTHS: ± 0.1 ft FROM GROUND SURFACE

SPACE TO ATTACH ENTIRE SOIL BORING LOG  
(SHOW SCREENED INTERVAL AND FILTER PACK INTERVAL.)





IOWA DEPARTMENT OF NATURAL RESOURCES  
**MONITORING WELL/PIEZOMETER CONSTRUCTION DOCUMENTATION FORM**

Disposal Site Name: IPL - Ottumwa Generating Station Permit No.: \_\_\_\_\_

Well or Piezometer No: MW-309

Dates Started: 10/27/16 Date Completed: 10/27/16

A. SURVEYED LOCATIONS AND ELEVATIONS	B. SOIL BORING INFORMATION
Locations ( $\pm 0.5$ ft): _____	Name & Address of Construction Company: _____
Specify corner of site: <u>NE of Parcel 003052620204000</u>	<u>Cascade Drilling, LP</u>
Distance & direction along boundary: <u>480' W</u>	<u>301 Alderson St</u>
Distance & direction from boundary to wall: <u>438' S</u>	<u>Schofield, WI 54476</u>
Elevations ( $\pm 0.01$ ft MSL): _____	Name of Driller: <u>Mike Mueller</u>
Ground Surface: <u>652.45</u>	Drilling Method: <u>HSA</u>
Top of protective casing: <u>654.97</u>	Drilling Fluid: <u>NA</u>
Top of well casing: _____ <u>654.94</u>	Bore Hole Diameter: <u>8 inch</u>
Benchmark elevation: _____	Soil Sampling Method: <u>Spoon</u>
Benchmark description: _____	Depth of Boring: <u>27.5 ft</u>

C. MONITORING WELL INSTALLATION	
Casing material: <u>PVC sch 40</u>	Placement method: <u>Gravity</u>
Length of casing: <u>21.5 ft</u>	Volume: <u>600 lbs</u>
Outside casing diameter: <u>2.38"</u>	Backfill (if different from seal): _____
Inside casing diameter: <u>2"</u>	Material: _____
Casing joint type: <u>threaded</u>	Placement method: _____
Casing/screen joint type: <u>threaded</u>	Volume: _____
Screen material: <u>PVC</u>	Surface seal design: _____
Screen opening size: <u>0.010"</u>	Material of protective casing: <u>Steel 6 inch</u>
Screen length: <u>5 ft</u>	Material of grout between protective casing and well casing: <u>sand</u>
Depth of well: <u>26.5 ft</u>	Protective cap: _____
Filter Pack: _____	Material: <u>Steel, vented</u>
Material: <u>Red Flint</u>	Vented: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No      Locking: <input type="checkbox"/> Yes <input type="checkbox"/> No
Grain size: <u>#40</u>	Well Cap: _____
Volume: <u>200 lbs</u>	Material: <u>PVC</u>
Seal (minimum 3 ft length above filter pack): _____	Vented: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Material: <u>3/8 inch bentonite chips</u>	

D. GROUNDWATER MEASUREMENT ( $\pm 0.01$ ft below top of inner well casing)	
Water level: <u>9.87</u>	Stabilization Time: <u>5 minutes</u>
Well development method: <u>surged with bailer and pumped</u>	
Average depth of frostline: <u>3.5'</u>	

**Attachments: Driller's log, Pipe schedules and grouting schedules. 8 1/2x11 inch map showing locations of all monitoring wells and piezometers.**


**Please mail completed for to:** Iowa Department of Natural Resources, Land Quality Bureau, 502 E 9<sup>th</sup> St, Des Moines IA 50319-0034.


**Questions? Call or Email:** Nina Koger, Environmental Engineer Sr., 515-281-8986, [Nina.Koger@dnr.iowa.gov](mailto:Nina.Koger@dnr.iowa.gov)



ELEVATIONS: ± 0.01 ft MSL  
DEPTHS: ± 0.1 ft FROM GROUND SURFACE

SPACE TO ATTACH ENTIRE SOIL BORING LOG  
(SHOW SCREENED INTERVAL AND FILTER PACK INTERVAL.)





# Appendix C

## Historical Monitoring Results

## Single Location

Name: IPL - Ottumwa Generating Station

Location ID: MW-307				
Number of Sampling Dates: 3				
Parameter Name	Units	4/8/2019	10/23/2019	12/11/2019
Boron	ug/L	240	200	190
Calcium	mg/L	240	230	230
Chloride	mg/L	220	220	200
Fluoride	mg/L	0.28	<0.23	<0.23
Field pH	Std. Units	6.76	6.68	6.37
Sulfate	mg/L	100	95	92
Total Dissolved Solids	mg/L	1000	1000	1000
Antimony	ug/L	--	--	<0.53
Arsenic	ug/L	--	--	<0.75
Barium	ug/L	--	--	140
Beryllium	ug/L	--	--	<0.27
Cadmium	ug/L	--	--	<0.039
Chromium	ug/L	--	--	<0.98
Cobalt	ug/L	--	--	11
Lead	ug/L	--	--	0.71
Lithium	ug/L	--	--	12
Mercury	ug/L	--	--	<0.1
Molybdenum	ug/L	--	--	<1.1
Selenium	ug/L	--	--	<1
Thallium	ug/L	--	--	<0.27
Total Radium	pCi/L	--	--	2.46
Radium-226	pCi/L	--	--	1.65
Radium-228	pCi/L	--	--	0.81
Field Specific Conductance	umhos/cm	1599	1684	1576
Field Temperature	deg C	12.47	13.38	11.5
Groundwater Elevation	feet	654.9	651.89 ft	649.59
Oxygen, Dissolved	mg/L	0.51	0.25	0.18
Turbidity	NTU	26	12.5	43.13
pH at 25 Degrees C	Std. Units	6.7	7.5	6.7
Field Oxidation Potential	millivolts	-3.7	-24.8	-45.8


**Single Location****Name: IPL - Ottumwa Generating Station**

Location ID: MW-308				
Number of Sampling Dates: 3				
Parameter Name	Units	4/8/2019	10/23/2019	12/11/2019
Boron	ug/L	190	220	160
Calcium	mg/L	240	240	220
Chloride	mg/L	160	160	150
Fluoride	mg/L	<0.23	<0.23	<0.23
Field pH	Std. Units	6.9	6.78	6.55
Sulfate	mg/L	300	300	280
Total Dissolved Solids	mg/L	1200	1100	1100
Antimony	ug/L	--	--	<0.53
Arsenic	ug/L	--	--	<0.75
Barium	ug/L	--	--	130
Beryllium	ug/L	--	--	<0.27
Cadmium	ug/L	--	--	<0.039
Chromium	ug/L	--	--	5.9
Cobalt	ug/L	--	--	0.26
Lead	ug/L	--	--	0.52
Lithium	ug/L	--	--	16
Mercury	ug/L	--	--	<0.1
Molybdenum	ug/L	--	--	<1.1
Selenium	ug/L	--	--	<1
Thallium	ug/L	--	--	<0.27
Total Radium	pCi/L	--	--	2.73
Radium-226	pCi/L	--	--	1.54
Radium-228	pCi/L	--	--	1.19
Field Specific Conductance	umhos/cm	1539	1637	1532
Field Temperature	deg C	12.54	13.16	10.5
Groundwater Elevation	feet	653.7	651.31	647.39
Oxygen, Dissolved	mg/L	0.66	4.42	0.43
Turbidity	NTU	6.87	7.42	15.72
pH at 25 Degrees C	Std. Units	6.8	7.9	6.8
Field Oxidation Potential	millivolts	-23	-38.7	-56.6

## Single Location

Name: IPL - Ottumwa Generating Station

Location ID: MW-309				
Number of Sampling Dates: 3				
Parameter Name	Units	4/8/2019	10/23/2019	12/11/2019
Boron	ug/L	1500	1300	1100
Calcium	mg/L	160	150	150
Chloride	mg/L	72	74	66
Fluoride	mg/L	0.27	<0.23	<0.23
Field pH	Std. Units	7.18	6.98	6.67
Sulfate	mg/L	410	400	370
Total Dissolved Solids	mg/L	1100	1100	980
Antimony	ug/L	--	--	<0.53
Arsenic	ug/L	--	--	1.1
Barium	ug/L	--	--	54
Beryllium	ug/L	--	--	<0.27
Cadmium	ug/L	--	--	0.09
Chromium	ug/L	--	--	1.7
Cobalt	ug/L	--	--	3.7
Lead	ug/L	--	--	2.8
Lithium	ug/L	--	--	8.2
Mercury	ug/L	--	--	<0.1
Molybdenum	ug/L	--	--	<1.1
Selenium	ug/L	--	--	<1
Thallium	ug/L	--	--	<0.27
Total Radium	pCi/L	--	--	1.77
Radium-226	pCi/L	--	--	1.08
Radium-228	pCi/L	--	--	0.683
Field Specific Conductance	umhos/cm	1396	1461	1350
Field Temperature	deg C	12.4	12.83	11.5
Groundwater Elevation	feet	653.55	651.28	647.24
Oxygen, Dissolved	mg/L	0.66	0.36	0.26
Turbidity	NTU	72.1	42.6	413.6
pH at 25 Degrees C	Std. Units	7.2	7.2	7.1
Field Oxidation Potential	millivolts	-3.3	-27.5	-37.8



# Appendix D

## Statistical Evaluation

## **APPENDIX D – STATISTICAL EVALUATION**

### **2019 Annual Report Addendum**

### **Ottumwa Generating Station Zero Liquid Discharge Pond**

Statistical evaluation completed in 2019 included the following:

- Evaluation of April 2019 detection monitoring results
- Evaluation of October 2019 detection monitoring results (finalized in January 2020)

The April 2019 results evaluation was based on interwell UPLs previously calculated for the OGS Ash Pond using the background monitoring data from upgradient well MW-301. This is a shared background well included in the monitoring systems for both the Main Ash Pond and the Zero Liquid Discharge Pond. The UPL calculations were provided in the 2018 Annual Report Addendum for the OGS Ash Pond.

The assessment monitoring results for December 2019 were evaluated in 2020.

I:\25222072.00\Deliverables\2019 Fed Annual Report Addendum - OGS ZLDP\Appendix D - Statistical Evaluation\2019\_ZLDP Addendum\_stats\_cover page.docx

